

Joists for polymer cables

Slip-on joints for polymer cables up to 550 kV

Variety of joints for your individual application needs


To assist you in the selection of the appropriate type of joint for your application, we have compiled an application table as given below.

specifications. All joints are designed so that direct- or indirect earthing, straight through connection or cross bonding can be realised.




High flexibility in earthing

Earthing of our joints can be made according to customer

Applications of joints for polymer cables

Type	Radial moisture barrier	Mechanical protection	Advantages	Application
MP / MPSP 	Steel housing	Steel housing and protection box	<ul style="list-style-type: none"> • Highest degree of mechanical protection • Excellent sealing against moisture 	<ul style="list-style-type: none"> • In all types of laying, such as in tunnels, concrete pits or directly buried installations • In installations with permanent humidity or shallow water

Types of earthing of joints for polymer cables

Type	Screen connection	Application
-21 	Straight through connection, insulated to ground	Direct connection of cable screen without cross bonding
-21sp 	Straight through connection with direct or indirect earthing	Connection of cable screen to earthing link
-31 	Screen interruption, insulated to ground for cross bonding	Cross bonding of cable screen at the joint

Technical data of joints for polymer cables

Operating voltage U_{max}/kV	\varnothing over XLPE insulation mm	Max. conductor cross-section (Cu/Al) mm ²	Max. \varnothing of outer sheath mm	Type	Mechanical protection and radial moisture barrier
300	67 - 120	2500	150	MPSP 1.300-21/-21sp/-31	Steel housing with protection box
420	81 - 120	2500	175	MPSP 1.420-21/-21sp/-31	Steel housing with protection box
550	99 - 129	2500	175	MPSP 1.550-21/-21sp/-31	Steel housing with protection box